
Due to high demand, expect some shipping delays at this time - orders may not ship for up to 2-3 business days. Skip to main content

- Shop
- Learn
- Blog
- Forums
- LIVE!
- AdaBox
- <u>IO</u>

toggl	e menu	
0		

- Sign In | Create Account
 New Guides
- Series
- Wishlists



- Forums
- AdaBox
- Ю


<u>Sign In</u> <u>0</u>

 Explore & Learn Learn Categories view all

- 3D Printing
- AdaBox
- Adafruit Products
- Arduino Compatibles
- Breakout Boards
- Circuit PlaygroundCircuitPython
- CLUE
- Community Support
- o Components
- Crickit
- Customer & Partner Projects
- Development Boards
- Educators
- EL Wire/Tape/Panel
- Feather
- Gaming
- Hacks
- Internet of Things IOTLCDs & Displays
- <u>LEDs</u>
- Machine Learning
- MakeCodeMaker Business
- o micro:bit
- Microcontrollers
- Programming
- Projects
- o Raspberry Pi
- Robotics & CNC
- o Sensors
- STEMMA
- Tools
- Trellis
- Wearables


Seriesview all

- Circuit PlaygroundAdafruit IO Basics
- o Collin's Lab



STEMMA Plug-n-play components <u>Get connected</u>

• New Guides



Using Melexis MLX90614 Non-Contact Sensors



Using Melexis MLX90614 Non-Contact Sensors

By lady ada

Tell temps without touching!

- Overview
- Wiring and Test
- Downloads
- Featured Products
- <u>Multiple pages</u><u>Download PDF</u>

Feedback? Corrections?

Overview

Save Subscribe

New Subscription

Please sign in to subscribe to this guide.

You will be redirected back to this guide once you sign in, and can then subscribe to this guide.


Close



This cyber-tronic looking sensor hides a secret behind it's glimmering eye. Unlike most temperature sensors, this sensor measures infrared light bouncing off of remote objects so it can sense temperature *without* having to touch them physically. Simply point the sensor towards what you want to measure and it will detect the temperature by absorbing IR waves emitted. Because it doesn't have to touch the object it's measuring, it can sense a wider range of temperatures than most digital sensors: from -70°C to +380°C! It takes the measurement over an 90-degree field of view so it can be handy for determining the average temperature of an area.



This sensor comes in an easy-to-use metal can. You can easily solder it or plug it into a breadboard. The four pins are used for power, ground, i2c clock and i2c data. There are two versions, one for 3V power and logic levels and one for 5V power and logic levels. You'll also want two 10K pull-up resistors for the I2C data lines, which we thoughtfully include.




Some specifications

- · Factory calibrated
- -40°C to +125°C for sensor temperature
- -70°C to +380°C for object temperature
- ±0.5°C accuracy around room temperatures
- High accuracy of 0.5°C over wide temperature
- 90° Field of view
- 5V version: 4.5 to 5.5V power
- 3V version: 2.6 to 3.6V power
- I2C interface, 0x5A is the fixed 7-bit address

Wiring and Test

Pinout




Despite being in an odd casing, the sensor is a lot like a simple sensor in a 'classic' integrated circuit shape. There are four pins. The datasheet has a diagram from the **bottom view** of the sensor which is a little annoying to refer to when wiring so use this image above.

Arduino Wiring

You can easily wire this sensor to any microcontroller, we'll be using an Arduino

This sensor uses a slightly non-standard type of I2C called "repeated-start". If you are not using an Arduino, make sure your microcontroller can support "repeated start I2C requests"!



Note the tab is how we will keep track of pins, in this wiring image, the tab is on the south side of the sensor, there's a red arrow pointing to it

- Connect GND to common power/data ground
- Connect **PWR** to the power supply, for the 3V sensor this is about 3.3V. For the 5V version, use about 5VDC
- Connect the SDA pin to the I2C data SDA pin on your Arduino. On an UNO & '328 based Arduino, this is also known as A4, on a Mega it is also known as digital 20 and on a Leonardo/Micro, digital 2
- Connect the SCL pin to the I2C clock SCL pin on your Arduino. On an UNO & '328 based Arduino, this is also known as A5, on a Mega it is also known as digital 21 and on a Leonardo/Micro, digital 3

The MLX90614 has a fixed I2C address, you can only connect *one* sensor per microcontroller!

Download Adafruit MLX90614

To begin reading sensor data, you will need to <u>download Adafruit MLX90614 from our github repository</u>. You can do that by visiting the github repo and manually downloading or, easier, just click this button to download the zip <u>Download the Adafruit MLX90614 Library</u>.

Rename the uncompressed folder $Adafruit_MLX90614$ and check that the $Adafruit_MLX90614$ folder contains $Adafruit_MLX90614.cpp$ and $Adafruit_MLX90614.h$

Place the **Adafruit_MLX90614** library folder your **arduinosketchfolder/libraries**/ folder. You may need to create the **libraries** subfolder if its your first library. Restart the IDE.


We also have a great tutorial on Arduino library installation at: http://learn.adafruit.com/adafruit-all-about-arduino-libraries-install-use

Load Demo

Open up File->Examples->Adafruit_MLX90614->mlxtest and upload to your Arduino wired up to the sensor



Now you can open up the serial console to see the ambient and object temperature printed out. Ambient temperature is the temperature of the sensor itself. The object temp is what its measuring in the 90-degree field of view.



Downloads

You can grab the datasheet here, it has a lot more details about the MLX90614

This guide was first published on Feb 28, 2014. It was last updated on Feb 28, 2014.

Difficulty: Beginner Guide Type: Project

Categories: Sensors/Temperature & Humidity

26 Saves

Featured Products



Melexis Contact-less Infrared Sensor - MLX90614 3V \$15.95





Melexis Contact-less Infrared Sensor - MLX90614 5V \$15.95 Add to Cart






DIY Thermal Light Painting - Heat Map Photography
By Ruiz Brothers
58


Intermediate



I2C addresses!
By lady ada
94
Beginner




TTL Serial Camera
By <u>lady ada</u>
106




EL Wire By <u>lady ada</u> 95 Beginner



Hacking the Kinect By lady ada 109 Intermediate




BeagleBone
By lady ada
16



Adafruit LED Backpacks

By <u>lady ada</u> 148



SMT Manufacturing By lady ada 30 Intermediate

×

OUT OF STOCK NOTIFICATION

YOUR NAME	
YOUR EMAIL	
NOTIFY ME	
Search	


Search

Categories

No results for query

- <
- (
- >
- Contact Us
- Tech Support Forums
- <u>FAQs</u>
- Shipping & Returns
- Terms of Service
- Privacy & Legal
- About Us
- Press
- Educators
- <u>Distributors</u>
- Jobs
- Gift Cards

[&]quot;I long to accomplish a great and noble task, but it is my chief duty to accomplish humble tasks as though they were great and noble" Helen Keller



A Minority and Woman-owned Business Enterprise (M/WBE)